High-Speed Degausser

Garner's high-speed and economical hard drive degausser is made with the same high quality components as our other products. This compact, lightweight degausser generates a 10,000 gauss magnetic field to permanently erase all data from hard drives and tape in 8 seconds.

Easy to use, simply place the media in the drawer. Closing the drawer automatically starts the degauss cycle.

The HD-2XT is designed to integrate with Garner's exclusive IRONCLAD® Erasure and Destruction Verification System with JPG image capture for complete, permanent and verifiable data elimination. Only Garner offers complete hard drive erasure with JPG images and reports of degaussed hard drives, providing the best audit trail and proof-of-erasure and destruction reports available.

Regulatory Compliance

The HD-2XT will help you meet government and industry standards requiring complete erasure of sensitive data prior to disposal, including:

- **CCPA** (California Consumer Privacy Act)
- **DoD** Up to Secret Classification
- **GDPR** (General Data Protection Regulation)
- **GLBA** (Gramm-Leach-Bliley Act)
- **HIPAA** (Health Information Portability and Accountability Act)
- **IRS 1075**
- **NIST SP 800-88r1**
- **PCI DSS 3.2** (Payment Card Industry Data Security Standard)
- **PIPEDA** (Personal Information Protection and Electronic Documents Act)
- **TAA** compliant

Features and Benefits

- » Erases up to 1,920 (1.8 in.), 960 (2.5 in.), and 240 (3.5 in.) drives per hour
- » Generates 10,000+ gauss (1 tesla) magnetic field for complete erasure of hard drives and tape
- » Complete data erasure in 8 seconds
- » Continuous duty — no cool down between cycles required
- » Plugs into a standard wall outlet worldwide
- » Office quiet

Safety Certifications

Garner's products are independently tested to stringent worldwide safety standards. Our resulting certifications and listings identify Garner products as safe to operate in data centers, hospitals, offices, and other sensitive environments around the world.

Garner's products are: ETL Listed • UL, IEC, CSA, CE and RCM certified • FCC compliant.

Erasure Verification

Built-in field verification checker: system and on-board diagnostics confirm the magnetic field strength of every erase cycle, ensuring complete erasure.

LCD display: Provides numerical value of gauss field strength after each cycle.

SCAN-1X Media Destruction Report software and scanner (option)**:** Creates a media destruction report complete with date, time, user ID, serial number, and erasure verification of each degauss cycle.

IRONCLAD Integrated Auditing System (option): Generate the ultimate proof-of-erasure and destruction reports with JPG images of the media and numerical documentation of the gauss field strength.

CERTIFICATE OF ERASURE & DESTRUCTION

Serial No.:	9VYK238J
Incident No.:	01
Date/Time:	2019-11-08 22:10:23
Degaussed:	10000 G (PASS)
Destroyed:	PD-5: 24 mm SSD: No
User ID:	1123
Witness ID:	N/A
JPG File:	20191108-220911_9VYK238J.jpg
JPG File 2:	20191108-221015_9VYK238J.jpg

GarnerProducts.com
Tel: 916-784-0200   Fax: 916-784-1425

10620 Industrial Avenue, Suite 100, Roseville, CA 95678

1-800-624-1903
Prices and specifications subject to change without notice.

©2022 Garner Products, Inc. All rights reserved.   2022-10-28

Packages

Configure a system to match your needs. Pair the HD-2XT high-speed degausser with our PD-5 NSA Listed physical destroyer. Complete your destruction work station by adding our custom built cart, case, or workstation table.

Our cases and carts are designed to give you field mobility in every type of situation from the office to the battlefield. Our workstation table is lightweight and features a locking cabinet for storing media.

Data Eliminator Cart Package (RCC-25SSD IRONCLAD with optional bins)

Degauss, Destroy, Recycle Workstation package (DDR-25SSD IRONCLAD)

Degauss, Destroy Mobility Package (DDM-25SSD)

Optional Accessories

IRONCLAD Erasure Verification System

SCAN-1X Media destruction software and scanner

CASE-HD2XIC MIL SPEC Shipping Case

Recycle Bin

"Degaussed" Labels

Media Bins

SPECIFICATIONS	
Ordering Information	**HD-2XT:** North America **HD-2XTA:** LATAM **HD-2XTE:** APAC, EMEA
Certifications/Listing	ETL Listed • ETL Listed • UL, IEC, CSA, CE and RCM certified • FCC and TAA compliant
Magnetic Field	1 tesla (10,000 gauss) nominal
Erasure Verification	IRONCLAD optional SCAN-1X optional
Charge Time	8 seconds (nominal)
Throughput (Hard drives per hour)	Up to 1920 (1.8 in.) Up to 960 (2.5 in.) Up to 240 (3.5 in.)
Media	Hard drives: Laptop, standard, network up to 1.25 in. in height* Tape media: All LTO, all DLT, AIT, 2590 Series, 8mm, and others
Power Requirement	90-250VAC ±5%, 50/60 Hz
Power Consumption	During standby: 17W During charge: 145W (avg) At the time of erase: 17W
Degausser System	Capacitive discharge
Duty Cycle	Continuous
Media Drawer Capacity (HxWxD)	1.25 x 4.3 x 5.9 (in.) 31.8 x 108 x 148.6 (mm)
Temperature	41°F - 104°F (5°C - 40°C)
Humidity	10%H - 40%H without condensation
Weight	34 lbs. (15.44 kg)
Size (HxWxD)	6 x 17.8 x 13.3 (in.) 151.1 x 450.9 x 337.8 (mm)
Warranty	**HD-2XT:** One-year manufacturer's limited warranty standard, optional three-year limited warranty available. **HD-2XTA/HD-2XTE:** One-year manufacturer's limited warranty standard.
Made in the USA	By Garner Products, Inc.

* All mounting hardware must be removed prior to degaussing.

Note: Hard drives and some tapes are not reusable after being degaussed.